

Agitating Ultrasonic Cleaning Systems

AgiSonic

- 348, 466, 765 Liter Capacities
- Max Platform Load up to 230 kg.
- Max Working Dims of 1,117mm x 914mm x 635mm Deep, 432mm Liquid Level
- High Performance Ultrasonics- Universal "U1B" Transducers
- Automated Hoist Transfer System Available for Multi-Tank Designs
- Liquid Level Protection for Heaters, Pump, and Ultrasonics
- Stainless Steel Tanks, and Plumbing
- Filtration and Oil Skimmer
- PLC / HMI
- Standard 208V, Three Phase Power



RANSOHOFF



**BLACKSTONE-NEY
ULTRASONICS**



CTG ASIA

Technical Specifications AgiSonic 3000 AgiSonic 4000 AgiSonic 5000

Liter Capacity	348	466	765
Maximum Parts Load	57kg	57kg	227kg
Ultrasonics (40kHz)	3,000 W	4,000W	5,000W
Heat	6,000 W	9,000W	12,000W
Power Requirement	208V, 3Ø, 60Hz	208V, 3Ø, 60Hz	208V, 3Ø, 60Hz
Amperage	30 FLA	45 FLA	50 FLA
Total Liquid Depth	610mm	610mm	610mm
Working Agitation Depth	432mm	432mm	432mm
Agitation Stroke	51mm - 152mm	51mm - 152mm	51mm - 152mm
Shop Air Required	6 Bar	6 Bar	6 Bar
Working Tank (LR x FB)	787mm x 559mm	889mm x 686mm	1,118mm x 914mm
Basket (LR x FB)	660mm x 457mm	762mm x 584mm	1,016mm x 762mm

Note: Basket height (203mm)

powered by



generators.



RANSOHOFF



**BLACKSTONE-NEY
ULTRASONICS**



CTG ASIA